

MATERIAL SAFETY DATA SHEET

MaxiFoam® XCL™ 34-600



General description

MaxiFoam® XCL™ 34-600 is built for more demanding handling situations where extra durability is needed. The robust foam nitrile palm coating offers strong abrasion resistance, and its textured surface helps improve grip when working with slippery or coated components.

The seamless liner provides everyday comfort, while the glove's tougher construction makes it a dependable option for regular industrial use in oily environments.

Compliances

ATG®, hereby declares, that this PPE Type is in conformity with the relevant Union harmonisation legislation: Regulation (EU) 2016/425 and the relevant harmonized standards No.: EN ISO 21420:2020 - General requirements, EN 388:2016 + A1:2018.

Use

Work glove for mechanical protection in dry environments.

For detailed applications where this product can be used please consult the ATG® website at www.atg-glovesolutions.com.

Main ingredients

Liner: Nylon, Spandex

Hazardous ingredients

REACH

All ingredients used in the manufacturing and construction of this product are compliant with the EU directive for the "Regulation of chemicals and their safe use" more commonly known as REACH -- EU directive EC 1907/2006. REACH stands for "Registration, Evaluation, Authorisation and Restrictions of Chemical substances". The key aim of REACH is to provide high levels of protection to human health and the environment.

More information can be found at: <https://single-market-economy.ec.europa.eu/sectors/chemica>.

OEKO-TEX®

This product has been tested and successfully passed the OEKO-TEX® STANDARD 100 global standard which indicates that the product is skin friendly. Look for the OEKO-TEX® logo to make sure you are buying a skin safe product.

More information can be found at: www.oeko-tex.com.

Precautions for use

Before usage, inspect the protective product for any defects or imperfections. If it is ripped or punctured during use, dispose of them immediately. Wear an appropriate size as too loose or too tight fitting products increase the risk for injuries.

Storage requirements

Store in a cool; dry place which is away from direct sunlight and/or heat. Extended exposure to direct sunlight or excessive heat will reduce shelf life and result in fading, discoloration and cracking. Normal anticipated shelf life is 5 years.

Disposal

After the product has been used it may be contaminated with infectious or other hazardous materials. Please dispose to local authority regulations.

Fire notes

The product will decompose at high temperatures. Extinguish using water, CO₂ spray or dry powder.

First aid

Remove contaminated PPE (Personal Protective Equipment). Skin contact: if an allergic reaction occurs seek medical advice immediately. Eye contact; rinse thoroughly with low pressure water. If any prolonged discomfort, seek medical advice immediately.

MATERIAL SAFETY DATA SHEET

MaxiFoam® XCL™ 34-600

Issue date: 01/10/2026

