

製品安全データシート

MaxiFlex® Elite™ 34-275

概要

Ultra-thin, ultra-light, and 30% thinner than standard foam nitrile gloves, MaxiFlex® Elite™ delivers maximum breathability and flexibility while still providing excellent durability and grip. At just 14 grams MaxiFlex® Elite™ is the perfect choice for high-precision tasks where extreme dexterity is needed.

コンプライアンス

ATG®, hereby declares, that this PPE Type is in conformity with the relevant Union harmonisation legislation: Regulation (EU) 2016/425 and the relevant harmonized standards No.: EN ISO 21420: 一般要求事項, EN 388:2016 + A1:2018.

使用方法

乾燥した環境での Precision Handling™ 向きの機械作業用手袋

本製品の詳しい使用方法についてはATG®社ウェブサイト参照してください。 www.atg-glovesolutions.com

主たる原材料

ライナー: ナイロン, Elastan

有毒物質の含有について

REACH

当社製品の製造加工過程で使用される物質はすべてREACH規制 (化学品とその安全な用法に関する規制、欧州議会理事会規則 EC1907/2006) を順守しています。REACHとは「Registration (登録) , Evaluation (評価) , Authorisation (認可) and Restriction (制限) of Chemical substances (化学品) 」の頭文字で、本規制の目的は人々の健康と環境を保全することにあります。詳細はウェブサイト参照してください。 <https://single-market-economy.ec.europa.eu/sectors/chemicals>

OEKO-TEX®

当社製品はエコテックス規格100認証取得により皮膚への優しさを保証しています。肌への安心を保証するOEKO-TEX®のロゴマークをご確認ください。

詳細はウェブサイト参照してください。 www.oeko-tex.com

使用上の注意

使用前は、保護製品に欠損あるいは不完全な部分がないかを点検してください。使用中に剥がれたり、あるいは穴が空いたりした場合は、すぐに処分してください。ゆったりしすぎたり、あるいはびったりしすぎたりすると、怪我をするリスクが高まりますので、適切なサイズを着用してください。

保管上の注意

直射日光や熱源を避け、乾燥した涼しい場所で保管してください。直射日光や高温に長期間さらされると、色落ちやひび割れの原因となりますのでご注意ください。

廃棄方法

使用済みの製品は、感染性物質やその他の有害物質に汚染されている可能性があります。地方自治体の規制に従って廃棄してください。

消火について

本製品は高温になると分解します。水、CO2スプレーまたは当社の乾燥粉末で消火してください。

救急処置

汚れた PPE (身体保護装置) は外してください。

発行日: 06/07/2026

