

MATERIAL SAFETY DATA SHEET

MaxiCut® Ultra™ (uncoated) 58-917



General description

MaxiCut® Ultra™ (uncoated) - Lightweight cut protection for layered safety.

MaxiCut® Ultra™ (uncoated) delivers high cut protection in a lightweight glove that can be worn alone or comfortably worn underneath other gloves for an added layer of safety and comfort. Designed for professionals who need enhanced protection without added bulk, it integrates the same CUTtech® technology found across the MaxiCut® range, ensuring reliable performance where cut risks are present.

The uncoated design enhances breathability and flexibility, keeping hands cool and comfortable even during extended wear. Its form-fitting construction supports natural movement and dexterity, allowing it to serve as either a standalone liner for light handling tasks or a base layer beneath coated gloves for tougher environments.

Combining lightweight comfort with dependable cut resistance, MaxiCut® Ultra™ (uncoated) gives you versatility, protection and performance in one streamlined glove.

MaxiCut® Ultra™ (uncoated) Lightweight Protection, Layered Confidence.

Compliances

ATG®, hereby declares, that this PPE Type is in conformity with the relevant Union harmonisation legislation: Regulation (EU) 2016/425 and the relevant harmonized standards No.: EN ISO 21420:2020 - General requirements, EN 388:2016 + A1:2018.

Use

Cut resistant work glove for Assured Protection™ in dry environments.

For detailed applications where this product can be used please consult the ATG® website at www.atg-glovesolutions.com.

Main ingredients

Liner: Polyester, Spandex, UHMWPE-Glass-Nylon

Hazardous ingredients

REACH

All ingredients used in the manufacturing and construction of this product are compliant with the EU directive for the "Regulation of chemicals and their safe use" more commonly known as REACH -- EU directive EC 1907/2006. REACH stands for "Registration, Evaluation, Authorisation and Restrictions of Chemical substances". The key aim of REACH is to provide high levels of protection to human health and the environment.

More information can be found at: <https://single-market-economy.ec.europa.eu/sectors/chemicals>.

OEKO-TEX®

This product has been tested and successfully passed the OEKO-TEX® STANDARD 100 global standard which indicates that the product is skin friendly. Look for the OEKO-TEX® logo to make sure you are buying a skin safe product.

More information can be found at: www.oeko-tex.com.

Precautions for use

Before usage, inspect the protective product for any defects or imperfections. If it is ripped or punctured during use, dispose of them immediately. Wear an appropriate size as too loose or too tight fitting products increase the risk for injuries.

Storage requirements

Store in a cool; dry place which is away from direct sunlight and/or heat. Extended exposure to direct sunlight or excessive heat will reduce shelf life and result in fading, discoloration and cracking. Normal anticipated shelf life is 5 years.

Disposal

After the product has been used it may be contaminated with infectious or other hazardous materials. Please dispose to local authority regulations.

Fire notes

The product will decompose at high temperatures. Extinguish using water, CO₂ spray or dry powder.

MATERIAL SAFETY DATA SHEET

MaxiCut® Ultra™ (uncoated) 58-917

First aid

Remove contaminated PPE (Personal Protective Equipment). Skin contact: if an allergic reaction occurs seek medical advice immediately. Eye contact; rinse thoroughly with low pressure water. If any prolonged discomfort, seek medical advice immediately.

Issue date: 01/10/2026

