


# PRODUCT DATA SHEET

## MaxiCut® Ultra™ 44-6745FI

|                     |                                             |
|---------------------|---------------------------------------------|
| Colour - Coating    | Black                                       |
| Colour - Liner      | Black                                       |
| Design              | Palm coated knitwrist                       |
| Liner               | Nylon, Polyester, UHMWPE, Spandex, Tungsten |
| Palm thickness (mm) | 1.30                                        |



### Dimensions

|                                  | 6 (XS) | 7 (S) | 8 (M)  | 9 (L) | 10 (XL) | 11 (2XL) | 12 (3XL) |
|----------------------------------|--------|-------|--------|-------|---------|----------|----------|
| A) Total glove length (+/- 5 mm) | 215    | 220   | 230    | 245   | 255     | 255      | 260      |
| B) Wrist length (mm)             | 64     | 64    | 75     | 79    | 81      | 82       | 82       |
| C) Wrist width (mm)              | 74     | 75    | 78     | 80    | 83      | 86       | 86       |
| D) Palm width (mm)               | 92     | 94    | 101    | 103   | 107     | 110      | 112      |
| Overlock colour                  | Blue   | Red   | Orange | White | Yellow  | Black    | Green    |

### EN Test Results

|                           | Notified body | Result/Pass |
|---------------------------|---------------|-------------|
| EN ISO 21420:2020+A1:2024 | TÜV Rheinland |             |
| EN 388:2016 + A1:2018     | TÜV Rheinland | 4243FP      |

### Typical Performance Values

|                                                      |               |
|------------------------------------------------------|---------------|
| EN ISO 21420:2020 - General requirements - Dexterity | Level 5       |
| EN 388:2016 + A1:2018 - A. Abrasion Resistance       | ≥ 8000 Cycles |
| EN 388:2016 + A1:2018 - B. Cut Resistance            | ≥ 2,5 index   |
| EN 388:2016 + A1:2018 - C. Tear Resistance           | ≥ 75 newtons  |
| EN 388:2016 + A1:2018 - D. Puncture Resistance       | ≥ 100 newtons |
| EN 388:2016 + A1:2018 - E. Cut Resistance ISO        | ≥ 30 Newton   |
| EN 388:2016 + A1:2018 - F. Impact Protection         | P             |

### HandCare®

Skin Health Alliance Dermatologically Accredited

REACH compliant

Sanitized®

OEKO-TEX® STANDARD 100

Washable 40°C/104°F



STANDARD  
100  
08.BH.57867  
Hohenstein HTTI  
www.oeko-tex.com

# PRODUCT DATA SHEET

## MaxiCut® Ultra™ 44-6745FI

### Special features

Impact Protection

Silicone free

Touchscreen Compatible



~~SILICONE~~



### Packaging

|                        |                 |
|------------------------|-----------------|
| Pairs per poly bag     | 6               |
| Poly bags per carton   | 12              |
| Carton count           | 72              |
| Carton dimensions (mm) | 500 x 295 x 350 |

### Weight

|                                  | 6 (XS) | 7 (S) | 8 (M) | 9 (L) | 10 (XL) | 11 (2XL) | 12 (3XL) |
|----------------------------------|--------|-------|-------|-------|---------|----------|----------|
| Glove weight / pair (+/- 6 gram) | 130    | 138   | 150   | 164   | 180     | 188      | 196      |
| Gross weight (kg)                | 10.30  | 11.00 | 11.80 | 12.80 | 13.90   | 14.50    | 15.10    |
| Carton weight (kg)               | 1.00   | 1.00  | 1.00  | 1.00  | 1.00    | 1.00     | 1.00     |
| Net weight (kg)                  | 9.30   | 10.00 | 10.80 | 11.80 | 12.90   | 13.50    | 14.10    |

Issue date: 16/07/2026

